

Prelam Particle Board

Modular Furniture are generally made out of prelam particle board as per industries standard.

On all exposed sides will be with 2mm PVC lipping and other sides will be 0.8mm / 0.5mm thick.

Standard table top height will be around 750mm.

Particle board and laminates are used from century ply / action tesa.

| Part | Thickness | Material | Type Of Board |
|-----------------|-----------|---------------------------------------|---------------|
| Table top | 25mm | Prelam particle board | OSL / BSL |
| Gable End | 25mm | Prelam particle board | BSL |
| Modesty panel | 25mm | Prelam particle board | BSL |
| | | | |
| Tiles | | | |
| | | | |
| Partition tiles | 9mm | Prelam particle board | OSL |
| Fabric tile | 9mm | MDF with fabric wrapping | BSR |
| Soft pinup tile | 9mm | Insulation with fabric wrapping | BSR |
| Marker tile | 9mm | MDF with marker laminate | BSR |
| Magnetic pinup | 9mm | MDF, Sheet metal with fabric wrapping | BSR |



Storage

| Storages | Thickness | Material | Type Of Board |
|---------------|-----------|-----------------------|---------------|
| Body | 18mm | Prelam particle board | OSL |
| Doors | 18mm | Prelam particle board | OSL |
| Back sheet | 9mm | Prelam particle board | OSL /BSB |
| Shelf's | 18mm | Prelam particle board | OSL /BSB |
| Тор | 18mm | Prelam particle board | OSL |
| Drawer bottom | 9mm | Prelam particle board | OSL /BSB |
| Skirting Ht | 65mm | | |
| Levelers | 10-12mm | | |

OSL: One side laminate

BSL: Both side laminate

BSR: Both side rough

BSB: Both side balancing White



Ply Wood:

| Description | Thickness | Material | Type of board |
|----------------|----------------|---------------|---------------|
| Table Top | 25mm | Plywood Board | MR/BWP |
| Storage | 16mm | Plywood Board | MR/BWP |
| Laminate Sheet | 1mm / 0.8mm | | |

Plywood Grade :

MR : Moisture Resistance.

BWP : Boiling Water Proof Grade.

By default MR grade of ply used for tables & storages.

Hardware:

| Materials | Brand | |
|-----------------|-----------------------------|--|
| Hinges | Ebco / Hettich / Equivalent | |
| Locks | Ebco / Hettich / Equivalent | |
| Drawer channels | Ebco / Equivalent | |
| Handles | D Oval handle | |
| Pedestal wheels | PP | |



Glass Privacy Panels

- 1. Sandwich glass : 4mm clear colour glass + 0.38mm clear laminate + 4mm clear colour glass (making 8mm thick).
- 2. Side glass / Divider glass: 8mm thick (frosted / plain / toughened / sandwich).
- 3. Vishwas safety glass brand is used for sandwich glasses made out of saint gobain.
- 4. Option of sandwich glass is also available.
- 5. Saint gobain for dividers and other purpose.

Metal Item Material :

- CRCA : Cold Rolled Cold Annealed
- MS : Mild Steel

Powder coating thickness of 50 - 60 microns (based on type of colour and finish of the same). Metal cross bars of 40X20 cross section pipes.

| SI No. | Description | Thickness in mm / Gauge |
|--------|----------------------------------|----------------------------|
| | | Approximate |
| 1 | Open Office System | |
| | Metal Leg (50X50) | 1.2mm / 18 Gauge |
| | Metal Raceway | 1mm / 19 Gauge |
| | Raceway Plate | 0.8mm / 20 Gauge |
| | Cross Bar | 1.2mm / 18 Gauge |
| | Metal modesty panel | 1mm / 19 Gauge |
| | Power Pole (wire entry) | 0.8mm / 20 Gauge |
| 2 | 75mm Frame System | |
| | Frame Vertical | 1.5mm / 16 Gauge |
| | Frame Horizontal | 1.2mm / 18 Gauge |
| | Raceway Plate | 0.8mm / 20 Gauge |
| | Metal tile | 0.8mm / 20 Gauge |
| | Cantilever Brackets | 1.6mm / 16 Gauge |
| | Gable End Brackets | 1.6mm / 16 Gauge |
| | Divider Brackets | 1.6mm / 16 Gauge |
| | Trims | 1mm / 19 Gauge |
| 3 | Round table C Leg Understructure | 1.2mm / 18 Gauge |
| | | |
| 4 | | Body :0.8mm/20 Gauge |
| | Metal Storage & Pedestal | Door: 1mm/19 Gauge shutter |



Raw materials brand

Board Metal - Frame system Metal - Open Office Hardware (storage) Glass Accessories (KBT, CPU etc..) : Century, Action Tesa.

- : Tata & JSW.
- : Tata, JSW & Apollo.
- : Ebco / Equivalent.
- : Vishwa Glass & Saint Gobain.
- : Innofit.

Notes

- · Specifications are as per industry standard .
- Specifications may vary as per the source manufacturing standards.
- Colour differences are there batch to batch.
- Specifications can be customized as per the site requirement.
- Branded raw materials used only .